

**Govt. of India
Central water Commission
Office of the Executive Engineer
Middle Ganga Division – II
Kendriya Bhawan, Hall no. – 3, IInd Floor,
Aliganj, Lucknow.**

No. HQ - 2 / MGD-2/CWC/Lko/ 11-12 /

Date:

Notice Inviting Quotation

The Executive Engineer, Middle Ganga Division-2, Central Water Commission, Aliganj, Lucknow-226024 invites on behalf of the President of India, sealed item rate quotation from approved and eligible contractors of CPWD, Railways, MES, P&T (Civil) and State PWD/Govt. undertakings and local Development Authorities for Repair work at Sub Division, Moradabad office, under Middle Ganga Division – II, CWC, Lucknow, up to 1500 Hrs. of 30-08-2011. The quotation shall be opened on 01-09-2011 at 15.30 hours. Interested quotationers may participate in the quotation opening at 15.30 hours.

The work is estimated to cost Rs. 108668/- (Rupees One Lacs Eight Thousand Six Hundred Sixty Eight Only). This estimate, however, is given merely as a rough guide.

**Schedule of quantities for the Work
“Repair work at Sub Division, Moradabad office, under Middle Ganga Division – II,
CWC, Lucknow” Annx. - A**

Sealed quotations, duly superscribed, as “**Quotation for Repair work at Sub Division, Moradabad office, under Middle Ganga Division – II, CWC, Lucknow**” will be received in the office of the Executive Engineer, MGD-2, CWC, Kendriya Bhawan, Hall no. – 3, IInd Floor, Aliganj, Lucknow upto 15.00 hrs. of **30.08.2011** and shall be opened on **01.09.2011** at 15.30 hrs. in the presence of the quotationers or their representatives who may like to be present. Quotation received after stipulated date/time shall not be entertained.

(Executive Engineer)
MGD-2, CWC, Lucknow

TERMS AND CONDITIONS

1. A prospective quotationer requiring any clarification of the NIQ documents may notify the department in writing, which should reach the Executive Engineer in-Charge at least three days before the closing date. Written copies of the department's response (including an explanation of the query) will be sent to all prospective quotationers and this shall form part of the quotation document.
2. At any time prior to the deadline for submission of quotation, the department may for any reason, whether at its own initiative or in response to a clarification requested by a prospective quotationer, modify the NIQ documents by amendment in writing, which will be binding on all the quotationers.
3. The quotation prepared by the quotationer shall comprise the following components:
 - a) Specifications of the offered work as required in the quotation documents;
 - b) All the terms and conditions clearly indicating variation, if any, with quotation requirements;
 - c) Documentary evidence to establish that the Quotationer is eligible to quotation and is qualified to perform the contract if the quotation is accepted;
 - d) Earnest Money Deposit in prescribed form; and Original quotation
4. Prices shall be quoted in Indian Rupees only.
5. Arithmetical errors will be rectified on the following basis. If there is a discrepancy between the unit price and the total price that is obtained by multiplying the unit price and quantity, the unit price shall prevail and the total price shall be corrected. If there is a discrepancy between words and figures, the amount in words will prevail. If the supplier does not accept the correction of errors, its quotation will be rejected.
6. The department will evaluate and compare quotations which have been determined to be substantially responsive, satisfactory & up to mark.
7. The department reserves the right to split the work and award the same to more than one quotationer.
8. The quotationer shall not contact the department on any matter relating to its quotation, from the time of the quotation opening to the time the Contract is awarded. If the quotationer wishes to bring additional information to the notice of the department, it should do so in writing.
9. An affirmative determination will be a prerequisite for award of the work to the contractor.
10. The department reserves the right at the time of contract award to increase or decrease by up to 50% the quantity of goods and services originally specified in the Schedule of Quantities & Rates without any change in unit price or other terms and conditions.
11. The work done under this contract shall conform to the standards mentioned in the Technical Specifications.
12. The department or its representative shall have the right to inspect and/or to test the work done to confirm their conformity to the Contract specifications at no extra cost to the Department.
13. Earnest Money @ 2% should be deposited at the time of submission of quotation, in shape of Demand Draft in favour of the Executive Engineer, Middle Ganga Division-2, CWC, Lucknow.
14. Security deposit at @ 5% of the quoted amount and VAT as applicable from time to time will be deducted from the running and final bill. The EMD will be adjusted against security deposit.

15. The payment shall be made on the successful completion of the work and submission of bill.
16. The Income Tax as per codal provisions shall be deducted at source from the bill.
17. The payment will be made on CPWD-26/CPWD-24 form by crossed cheque/ draft payable on SBI, Main Branch, Lucknow.
18. Payment shall be made in Indian Rupees.
19. No materials including cement, steel and other building materials will be supplied by the department and the same to be arranged by the contractor himself duly got approved by the competent authority.
20. Any corrections/cuttings in the quotation document shall be initialed by the quotationer.
21. The contractor will provide suitable/congenial conditions and atmosphere, and maintain law and order during the execution of work.
22. The contractor shall comply with the provisions of relevant standards and code of practices like current edition ISI codes and shall own liabilities on account of default, if any.
23. Notwithstanding the contractors' obligation to comply with the requirement of the safety manual the contractors' attention is particularly drawn on the following requirements.
 - a) The contractor shall be responsible for providing operating and maintaining a first aid station at the site at his own cost for treatment of his employees.
 - b) Emergency treatment shall include carrying of emergency patient until transfer to a permanent hospital or other place of treatment.
24. On completion of the work to the satisfaction of Engineer-in-charge, the contractor shall remove all equipment, material temporary facilities remains, rubbish, debris and shall restore all these places to proper conditions to the satisfaction of the Engineer-in-charge.
25. The contractor should be well concerned with any statutory rules, regulations as may be prevalent in the respective territory and the contractor shall indemnify and keep the project free from and against such liability.
26. The contractor should ensure that local inhabitation/structures falling into vicinity of work are not disturbed while executing the job. Damage, if any, occurring due to negligence of the contractor shall be to his account.
27. The contractor shall make his own arrangement for electricity, and water required for both drinking and construction works.
28. The contractor shall provide an experienced foreman/supervisor and technicians to perform the work covered here in. The project authorities has the right to order the removal of any person from the work, who in his opinion are not qualified, unwilling or are unable to perform the work and responsibilities to the satisfaction of project authority.

(Executive Engineer)
MGD-2, CWC, Lucknow

Copy to:-

1. The Director, Software Dte., CWC, New Delhi on publicity through his website.
2. Notice Board, O/O CE, UGBO, CWC, Lucknow
3. Notice Board, MGD-I/II, CWC, Lucknow
4. The Superintending Engineer, HOC, CWC, Dehradun.
5. Assistant Engineer, Sub Division Moradabad.

Schedule of Rates

Annex. A

Name of Work: Repair work at Sub Division, Moradabad office, under Middle Ganga Division-II, CWC,Lucknow.

| S. N | Description | Unit | Qty. | Rate | Rate in words |
|-------------|--|-------------|-------------|-------------|----------------------|
| 1 | Dismantling roofing including ridges, hips valleys and gutters etc., and stacking the material within 50 metres lead of: G.S. Sheet | sqm | 20.00 | | |
| 2 | Centering and shuttering including strutting, propping etc. and removal of form for : Lintels, beams, plinth beams, girders, bressumers and cantilevers. | sqm | 4.15 | | |
| 3 | Brick work with F.P.S bricks of class designation 75 in superstructure above plinth level up to floor V level in all shapes and size in : C.M.1:6(1cement:6course sand) | cum | 8.77 | | |
| 4 | Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level :1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) | cum | 0.35 | | |
| 5 | Reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete. Cold twisted bars | kg | 46.21 | | |
| 6 | 12mm cement plaster of mix : 1:6 (1cement:6 coarse sand) | sqm | 42.12 | | |
| 7 | 15 mm cement plaster on rough side of single or half brick wall of mix : 1:6 (1 cement: 6 coarse sand) | sqm | 42.12 | | |
| 8 | Steel work welded in built up sections/framed work including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. : In gratings, frames, guard bar, ladder railings, brackets, gates and similar works. | Kg. | 35.64 | | |
| 9 | White washing with lime to give an even shade: New work (three or more coats) | sqm | 84.24 | | |
| 10 | Distemping with 1st quality acrylic washable distemper (ready made) of approved manufacturer and of required shade and colour complete. as per manufacturer's specification.One or more coats on old work. | sqm | 70.84 | | |
| 11 | Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40mm dia. M.S. tube 1.5 m centre to centre horizontal & vertical tubes joining with cup & lock system with M.S. tubes, M.S. tube challies, M.S. clamps and M.S. staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after .The scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge .The lavational area of the scaffolding shall be measured for payment purpose .The payment will be made once irrespective of duration of scaffolding. | sqm | 121.50 | | |

| S. N | Description | Unit | Qty. | Rate | Rate in words |
|------|--|------|-------|------|---------------|
| 12 | Providing and fixing false ceiling with 12 mm thick plain/ semi perforated or with design ceiling tiles of high density mineral fibre fixed to a grid made out of anodised aluminium(with 15 micron anodic coating) T-sections 35 x15x1.5 mm size main runners and cross runners 23.5x19x1.5 mm fixed to main runners placed 600 mm centre to centre both ways so as to form a grid of 600 mm square. The frame work shall be suspended from ceiling by level adjusting hangers of 6 mm dia M.S rod fixed to roof slab by means of ceiling cleats. The suspenders shall be placed 600x 1200 mm centre to centre including fixing to the frame with C.P brace screws and applying a priming coat of zinc chromate yellow primer (aluminium frame work shall be paid separately). | sqm | 37.85 | | |
| 13 | Providing and fixing False Ceiling Tiles of approved materials of size 595x595 mm in true horizontal level suspended on inter locking metal grid of hot dipped galvanised steel sections (galvanized @ 170 gsm/sqm.) consisting of main "T" runner suitably spaced at joints to get required length and of size 24x38mm made from 0.30mm thick (minimum) sheet spaced at 1200mm center to center and cross "T" of size 24x25mm made of 0.30mm thick (minimum) sheet, 1200mm long spaced between main "T" at 600mm center to center to form a grid of 1200x600 mm and secondary cross "T" of length 600mm and size 24x25mm made of 0.30 mm thick (minimum) sheet to be interlocked at middle of the 1200x600mm panel to form grids of 600x600mm and laying false ceiling tiles of approved texture in the grid including, wherever, required, cutting/making, opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc. Main "T" runners to be suspended from ceiling using GI slotted cleats fixed to ceiling with 6 mm dia and 50mm long dash fasteners, 4mm GI adjustable rods with galvanised level clips spaced at 1200m center to center along main T, bottom exposed width of 24mm of all T-sections shall be pre-paint | sqm | 37.85 | | |

Ex. Engineer, MGD-II, CWC, Lko.

Signature of Contractor
Date
Place
PAN No.: